

# **HD-NDI-TF**

## **NDI® HX Compatible Telephoto-Lens Streaming Camera**

The HD-NDI-TF adds another level of sophistication to the already versatile NDI® HX, leveraging its 5MP 5-50mm weatherproof lens. Encased sturdily into the case, comes a new one-of-a-kind varifocal lens capable of capturing footage up to 60ft, all while being IP54 rated for whatever mother nature wants to throw at it.

The HD-NDI-TF is yet another tool in the arsenal to express your creativity, no matter the boundaries of streaming limitations!



#### **KEY FEATURES:**









#### **APPLICATIONS:**



**ACADEMIC RESEARCH** 



WEATHER CAPTURE



**MACHINE VISION** 



OUTDOOR EVENTS



LIVESTREAM EVENTS

\*NDI® is a registered trademark of Newtek, Inc.



#### **MAIN FEATURES**

- Full-HD 1/3" Progressive Scan CMOS sensor capable of 1080 60p NDI® HX Video.
- Accessible Web UI to stream directly to social media platforms and control image parameters over IP.
- Versatile design with top and bottom tripod mounts for uniques shot creation.
- PoE+ adaptable with adapter (comes with purchase of the camera)

- Custom IP54 rated Varifocal lens providing a FOV of 51° wide, and 6.1° tele to help get that perfect shot.
- · Weatherproof rating allows for extra protection against environmental elements
- Small form-factor and rugged designed makes all video streaming applications possible
- Perfectly suited for outdoor shots any new or existing NDI® HX setup.

#### **SPECIFICATIONS**

**VIDEO** 

**Image Sensor** 1/3" Progressive CMOS **Sensor Size** 5.346mm x 3.003mm (16.9) **Effective Pixels** Horizontal: 1920, Vertical: 1080 **Pixel Size** a2.75  $\mu$ m (H) x 2.75  $\mu$ m (V) Resolution 1080p, 1080i, 720p

**Resolution Rate** 1080 60p/59.94/50p/30p/29.97p/25p

24p

1080 60i/59.94i/50i 720 60p/59.94p/50p

Output IP (NDI|HX/SRT/RTMP/RTSP)

**Color Space** 4:2:2 (YCbCr) 10bit

Min Illumination 0.2Lux (day), 0.1Lux (Night) White Balance Auto & Manual (9000 - 11,000 K) **LENS** 

Lens 5mm ~ 50mm Custom Lens FOV Wide: 51° Tele'd: 6.1°

**STANDARD** 

**IP Protocol** UDP|IP, RTSP|RTMP, SRT, NDI|HX

**PHYSICAL** 

**Camera Control** Protocol: VISCA Over IP

32°F - 104°F **Operation Temp** 

Dimension 73mm x 41mm x 41mm

2.86" x 1.61" x 1.61" (With added lens)

Weight 454q / 1 lb

**Power** 12VDC (+9 - +15VDC) (PoE Adapter Included)

### PACKAGE CONTENTS







DC 12v Power Supply & Sockets Adapter



Lens Hex Adapter

\*NDI® is a registered trademark of Newtek, Inc.

At ADIA Imaging, innovation is key to crafting our tried and tested quality imaging solutions. We strive to raise the bar by engineering and manufacturing cutting edge cameras and converters. From concept to reality, AIDA Imaging meticulously creates products that are applicable to various solutions, effective for the global user

<sup>\*</sup>Specification are subject to change without notice.