

TGEN-6P

Tri-level sync generator with precision

Synchronize your Genlock capable gear with the TGEN-6P Tri-level sync generator with precision. Adjustable V and H sync generation for more accurate pulse timing and switchable Master and Slave mode for cascading suitable for broadcast studio workflows..



KEY FEATURES:



APPLICATIONS:



LIVE PRODUCTION



WORSHIP



VIDEO CONFERENCE



MEDICAL



THEATER

MAIN FEATURES


- Multi format HD Tri Level Sync up to 1080p60.
- Both V Sync and H Sync generation for more accurate timing.
- Up to 6 synchronized reference output per device.
- Slave mode for cascading.
- Built in LCD screen.
- Built in setting dip-switches.
- Versatile, compact, and rugged design

SPECIFICATIONS

VIDEO		STANDARD	
Reference Out	Tri-Level HD	SMPTE	SMPTE 274M, SMPTE 296M
Format	1080p 60/59.94/50/30/29.97/25/24Hz 1080i 60/59.94/50Hz 720p 60/59.94/50/30/25/24Hz	PHYSICAL	
Accuracy	2ppm	Control	Dip-switches & Text LCD
Reference In	Tri-Level HD & Bi-Level SD	Operation Temp	32°F - 104°F
		Dimension	129mm x 86mm x 29mm / 5.07" x 3.38" x 1.10"
		Weight	278g / 0.61lbs
		Power	12VDC (+9 - +15VDC)

*Specification are subject to change without notice.

PACKAGE CONTENTS



DC 12v Power Supply & Sockets Adapter